



## Product Data Sheet

# ENGINE OIL SHPD 15W-40

### Product Description:

**ENGINE OIL SHPD 15W-40** is a fuel saving MID SAPS super high performance universal oil based on 100% synthetic technology designed for high loaded diesel engines in light- and heavy commercial vehicles working under severe operating conditions through the whole year for use in Euro-4, Euro-5 and Euro-6 engines equipped with a Diesel Particle Filter (DPF) and suited for diesel engines equipped with EGR and/or SCR after treatment system.

**ENGINE OIL SHPD 15W-40** is formulated with high refined base stock in combination with an unique additive package to reach the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against "Bore Polishing".
- Extended drain intervals.
- Complies with strictest European emission regulation.

**ENGINE OIL SHPD 15W-40** exceeds the following performance criteria:

ACEA E9/E7	MB-228.31	Volvo VDS-4	MAN M3575	MACK EO-O+
API CJ-4	Renault VI RLD-3	Cummins CES 20081	CAT ECF-3/2/1a	DCC PGOS 93K218
Deutz DQC III-05	MTU Type 2.1			

Properties	Unit	Test Method	Typical Value
SAE Grade		SAE J3000	15W-40
Density@15°C	kg/m <sup>3</sup>	ASTM D4052	873
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	112
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	14.9
Viscosity Index		ASTM D2270	135
Viscosity CCS @-20°C, max	cP	ASTM D2270	7000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	8.1
Sulphated Ash	%Wt	ASTM D874	0.96

Product Nr: 4251

Date Issued: 18-03-2016

Date Superseded: 01-01-2015

Revision nr: 1