



Product Data Sheet:

AUTOGEAR OIL MP 80W-140

Product Description:

AUTOGEAR OIL MP 80W-140 is a high performance gear lubricant designed to provide excellent lubrication in a wide range of automotive transmissions, axles and final drives where an API GL-5 oil is specified.

AUTOGEAR OIL MP 80W-140 is formulated from carefully selected base stocks and well balanced extreme pressure additives. **AUTOGEAR OIL MP 80W-140** gives excellent protection towards gear components regarding wear and scoring and provides very good anti-corrosion protection and has been carefully inhibited against the formation of foam.

AUTOGEAR OIL MP 80W-140 exceeds the specifications of API GL-5 and MIL-L-2105D, as well as the requirements of most “Original Equipment Manufacturers” (OEMs).

AUTOGEAR OIL MP 80W-140 is recommended for certain manual transmissions and final drives requiring oils meeting API GL-5 in on road passenger cars, light- and heavy duty trucks, buses and vans and is also recommended for off highway equipment, in construction, mining and agriculture.

Specifications:

Exceeds: API GL-5, US Army MIL-L-2105D

| Property: | Test Method: | Typical Values: |
|--|--------------|-------------------------|
| SAE Viscosity Grade | SAE J306 | 80W-140 |
| Density @ 15°C | ASTM D4052 | 897 kg/m ³ |
| Kinematic Viscosity @ 40°C | ASTM D7042 | 275 mm ² /s |
| Kinematic Viscosity @ 100°C | ASTM D7042 | 27.3 mm ² /s |
| Low-Temperature Brookfield Viscosity @ -26°C | ASTM D2983 | <150000 cP |
| Viscosity Index | ASTM D2270 | 145 |
| Flash Point | ASTM D92 | 190°C |
| Pour Point | ASTM D97 | -27°C |

Product nr: 4309

Date Issued: 08/0/2011

Date Superseded: 30/05/2011

Revision nr: 01